

# ED2-48/2S SERIES ED2SYS-48/2S SERIES

# **MULTI-SHELF HEATED DISPLAY**



ED2-48/2S



• HALO HEAT ... a controlled, uniform heat source that gently holds and surrounds food for better appearance, taste, and longer holding life.

• Holds and displays hot food fresh and moist for hours.

### • SELF-SERVICE HOT DISPLAY CASE

- Curved glass styling.
- Thermostatically controlled heat source radiates from the base of each shelf.
- Top shelf incorporates thermal kinetic glass technology to provide an evenly heated display surface.
- Bottom shelf is heated by an aluminum plate with a resistive heat pad.
- Overhead lighting on each shelf.
- Solar cool bronze sliding glass doors reflect heat back into the products and mirror the display to enhance merchandising effect.
- Customer self-service opening is across the full width of case.
- Front-mounted heat guard on each shelf provides customer protection.



ED2SYS-48/2S

### MULTI-SHELF HEATED DISPLAY CASE

The display case is constructed of 18 gauge, non-magnetic stainless steel. A curved, tempered glass top frames the display case. Removable, sliding glass doors on the operator side are included. Sliding door tracks have a "clean sweep" cutout allowing for easy cleaning and crumb removal. Each shelf is controlled by one (1) adjustable thermostat with a range of 1 to 10, and includes one (1) heat-on indicator light. The two-shelf self-service display system includes a low-profile, European style base with one (1) storage shelf. As an additional option, the base can be adapted to accommodate one (1) 500-1D drawer warmer. Counter-top display case includes one set of 4" (102mm) legs. **Note:** For use with pre-packaged foods only.

ED2-48/2S	- 48"	(1219mm)	lenoth
ED4"40/40	- 40	(14121111111	ingui

☐ **ED2SYS-48/2S** - 48" (1219mm) length, with base

### FACTORY INSTALLED OPTIONS

- The system base is not sold as a separate item. Order the full ED2SYS/2S model to receive the base.
- Panel Color Choices
  - **⇒**Specify color choice:
  - ☐ Black, standard
  - ☐ Stainless Steel
  - ☐ Custom Color










# ED2-48/2S SERIES ED2SYS-48/2S SERIES

**MULTI-SHELF HEATED DISPLAY** 







ED2-48/2S Profile

ED2SYS-48/2S Profile

ED2SYS-48/2S Back View

ELECTRICAL										
VOLTAGE	PHASE	CYCLE/HZ	AMPS	kW						
208-240V (AGCY)	1	50/60	11.7	2.8	NEMA 6-20P					
at 208V	1	50/60	10.0	2.1	20A, 250V PLUG					
at 240V	1	50/60	11.6	2.8	20A, 250 V PLUG					

WEIGHT (EST.)									
MODEL	NET	SHIP							
ED2-48/2S:	CONTACT FACTORY	305 lb (138 kg)							
ED2SYS-48/2S:	CONTACT FACTORY	405 lb (184 kg)							
CRATED DIMENSION	IS: HXWXD								
ED2-48/2S: CONTACT FACTORY									

### PRODUCT CAPACITY

ED2SYS-48/2S: CONTACT FACTORY

TOP SHELF

Twelve (12) chicken boats with dome cover

BOTTOM SHELF

Fifteen (15) chicken boats with dome cover

_			_		_				,					
ס	П	М	Е	Ν	S	I C	) N	IS	(H	[ X	W	Х	D	)

ED2-48/2S EXTERIOR:

30-3/16" x 48" x 48" (766mm x 1219mm x 1220mm)

ED2SYS-48/2S EXTERIOR:

47-7/8" x 48" x 48" (1216mm x 1219mm x 1220mm)

TOP SHELF DIMENSIONS (W X D):

42-3/4" x 18-3/4" (1085mm x 475mm)

**BOTTOM SHELF DIMENSIONS (W X D):** 

40-11/16" x 28-3/4" (1033mm x 730mm)

### **SPECIFICATIONS**

- Two (2) florescents are enclosed in the top interior of the case. Two (2) florescents are enclosed and centered under the top shelf. Each set is controlled by one (1) ON/OFF light switch.
- One (1) 10" x 36" (254mm x 914mm) operator-side work shelf.

## **OPTIONS & ACCESSORIES**

□ WORK SHELF WITH GRAVY LANE 5005638

### INSTALLATION REQUIREMENTS

Display case must be installed level. The display case must not be installed in any area where it may be affected by steam, grease, dripping water, high temperatures, or any other severely adverse conditions.

Do not install a heated display case near a cold air source such as a freezer, air conditioning vents, or in any area where outside air fluctuation can affect performance.



#70 - 05/09

W164 N9221 Water Street • P.O. Box 450 • Menomonee Falls, Wisconsin 53052-0450 • U.S.A. PHONE: 262.251.3800 800.558.8744 U.S.A./CANADA FAX: 262.251.7067 800.329.8744 U.S.A. ONLY

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com