

intelliFAX-5750e

NETWORK-READY
BUSINESS CLASS FAX
LASER

FEATURING

- Super G3, 33.6K bps High Speed Fax Modem
- Dual 250-Sheet Paper Trays standard, for a total paper capacity of 500 sheets
- 8MB Memory stores up to 600 Pages* for Out-of-Paper Reception and Memory Transmission
- Up to 15ppm Laser Engine for printing of faxes and copies
- Up to 50-Page Auto Document Feeder



8MB
MEMORY with
BROADCASTING

SUPER G3
33.6K bps High-Speed
FAX

500
SHEET
PAPER CAPACITY

At your side.™

brother®

intelliFAX-5750e

NETWORK-READY
BUSINESS CLASS FAX

LASER



Featuring...

- Super G3, 33.6K bps High Speed Fax Modem
- Dual 250-Sheet Paper Trays standard, for a total paper capacity of 500 sheets
- 8MB Memory stores up to 600 Pages* for Out-of-Paper Reception and Memory Transmission
- Up to 15ppm Laser Engine for printing of faxes and copies
- Up to 50-Page Auto Document Feeder
- 10/100 BaseTX Ethernet Network Print/Fax Server standard
- Quickly scan faxes as fast as 2 secs./page*
- 232 Station Auto Dialing (32 One-Touch Keys, plus up to 200 speed dial locations)
- High Yield Toner Cartridges deliver low printing costs per page†
- Fax Broadcasting to up to 282 Locations
- Multi-Copying up to 99 copies, plus Sorting
- Copy Reduction and Enlargement, 50%-200%

8MB
MEMORY with
BROADCASTING

DUAL
Scan a fax into memory while
another is being sent or received.
ACCESS

UP TO
6,000 PAGE
YIELD
TONER


500 SHEET
PAPER CAPACITY

Other Standard Features

- Dual Access capability lets you scan faxes into memory while the unit is busy sending or receiving
- 4-Day Battery Back-up for Fax Memory
- Fax Security with password controlled access
- Auto Fax/Tel Switching for receiving fax and voice calls on a single phone line
- Fax Forwarding, Paging and Remote Fax Retrieval
- Telephone Handset
- Caller ID and Distinctive Ring Detection ready‡
- Built-in Parallel and USB interfaces for future printing needs (cables not included)

BUILT-IN NETWORK PRINT/FAX SERVER

Provides scanning and internet faxing via E-mail*, plus network printing for small workgroups**.



◆ SMTP/POP3 E-mail server support required
◆◆ Support For:

- Windows® 2000 Professional TCP/IP
- Windows® XP TCP/IP
- Windows NT® 4.0 TCP/IP
- Windows® 95/98/98SE/Me TCP/IP Peer-To-Peer
- UNIX TCP/IP
- AppleTalk®
- Novell Netware®

* Based on Brother #1 Chart with JBIG coding and standard resolution.

† Based on 5% page coverage using optional TN460 Toner Cartridge (cartridge requires additional purchase).

‡ Requires additional purchase.

▲ Check with local phone company for availability of and charges for these services.

All trademarks and registered trademarks referenced herein are the property of their respective companies.

© 2002 BROTHER INTERNATIONAL CORPORATION, 100 Somerset Corporate Blvd., Bridgewater, NJ 08807-0911
For more information please call the Brother Fax-Back System at 1-800-521-2846 (USA ONLY)
or visit our web site at www.brother.com.

All specifications are subject to change without notice. Printed in USA. CATFX5750e

Download from www.Somanuals.com. All Manuals Search And Download.

PRODUCT SPECIFICATIONS

Approved:	UL and FCC
Unit Dimensions:	17.4" x 17.1" x 17.0"
Unit Weight:	31.1 lbs.
Carton Dimensions:	22.8" x 21.1" x 27"
Carton Weight:	50.7 lbs.
UPC Code:	0 12502 60284 2
Compatibility:	ITU-T Group 3
Coding Method:	MH/MR/MMR/JBIG
Modulation:	33600/31200/28800/26400/24000/ 21600/19200/16800/14400/ 12000/9600/7200/4800/2400 bps
Transmission Time:	As fast as 2 seconds per page (Brother #1 Chart, JBIG)
Printing Method:	Electrophotography
Copy Speed:	Up to 15 copies per minute
Document Input Width:	5.8" to 8.5"
Recording Paper Size:	8.5" x 11" / 8.5" x 14"
Scanning/Recording Width:	8.2"
Resolution Standard:	203 x 98 lines/inch
Fine Mode:	203 x 196 lines/inch
Superfine:	203 x 392 lines/inch
Display:	LCD, 2 lines by 16 characters
Gray Scale:	64 shades
Interfaces (Standard):	USB and High-Speed, Bi-Directional, Parallel Centronics (cables not included)
Dialing System:	Selectable Pulse/Tone
Speaker Type:	Monitor
Communication Source:	Public Switched Telephone Network
Connection Requirements:	USOC RJ11C Modular Jack (or equivalent)
Power Supply:	120V, 50/60 Hz
Power Consumption:	Average Operating (Copying): 350W Standby: 70W or less Sleep Mode: 10W or less
Noise Level:	53 dBA Printing 30 dBA Standby
Operating Environment:	50° to 90.5° F
Standard Toner Cartridge:	Up to 3,000 pages @ 5% coverage

OPTIONAL ACCESSORIES†

TN430:	Standard Yield Toner Cartridge (Up to 3,000 pages @ 5% coverage)
TN460:	High Yield Toner Cartridge (Up to 6,000 pages @ 5% coverage)
DR400:	Replacement Drum Unit

use only
GENUINE
brother
supplies

At your side.™
brother®

www.brother.com

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>